



Titebond Painter's Plus Caulk

Titebond® Painter's Plus is a high-quality, versatile siliconized acrylic caulk that is designed for both interior and exterior applications. It offers an excellent flexible, air-tight, water-resistant seal and provides a strong bond to most common building materials, including wood, metal, glass, masonry, aluminum and brick. It is ideal for sealing joints, repairing cracks and back-filling gaps.

Titebond Painter's Plus is de-aired for a smooth, uniform bead that extrudes and tools easily. It can be painted with a water-based interior paint with one coat and will not bleed through the paint. Titebond Painters Plus is a non-stringing formula that won't sag or drool and it has excellent bead cut-off. It also cleans up with water when wet.

Specifications

- White and colors exceed the requirements of ASTM C834 Type OP Grade -18°C
- Clear exceeds the requirements of ASTM C834 Type C Grade 0°C

Revised December 2012



Product Features

- Seals joints, repairs cracks and fills gaps
- Paints easily with one coat
- Provides a flexible, watertight seal
- Tools easily and cleans up with water
- No residual odor
- De-aired for a smoother bead
- Mildew resistant

Physical Properties

Type Acrylic

Color White, clear and colors

Solids 82% white, 60% clear, 87% colors

Viscosity 550,000 cps white, 600,000 cps clear, 500,000 cps colors

Freeze/thaw stability Stable

Non-reactive VOC 23 g/L (<1.5%) white, 5 g/L (<1.5%) clear, 21 g/L (<1.5%) colors

Weight/gallon 13.5 lbs. white, 8.9 lbs. clear, 13.9 lbs. colors

Flashpoint None

Storage life 24 months in tightly closed containers at 50°F to 80°F.

Coverage (maximum): Approximate length of bead according to bead diameter:

Container	1/4" bead	3/8" bead	1/2" bead
-----------	-----------	-----------	-----------

10.1 oz. Cartridge

31 ft.

14 ft.

8 ft.

Application Guidelines

Application Temperature Above 40°F and below 120°F.

Service Temperature Range -25°F. to 180°F. white and colors, 0°F to 160°F. clear.

Method of Application Cartridge/caulking gun

Working Time Approximately 10-15 minutes for a 1/4" bead

Working Surfaces Surfaces must be cleaned down to the original substrate, dry and free from oil, grease, water, dirt or any other material that may prevent adhesion.

Joint/gap specifications 1/2" maximum width and 1/4" maximum depth.

Cleanup Clean excess material with a damp cloth. Clean hands and tools with soap and water. Scrape dried excess.

Limitations

Do not apply if rain is expected within 12 hours. Titebond Painters Plus should be dry to the touch and ready to paint in 2-4 hours. Painter's Plus is not designed for continuous submersion or use below the waterline. For questions, please call our toll free Help Line 1-800-347-4583 or visit us at titebond.com.

Caution Statements

White

WARNING: EYE, SKIN AND RESPIRATORY IRRITANT. Contains acrylic polymer, limestone, titanium dioxide, ethylene glycol and mineral derivatives. Harmful if swallowed. Long term exposure to ingredients in this product can increase the risk of certain cancers. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate personal protective equipment. **First Aid:** If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush eyes with water for 15 minutes; contact physician. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Material Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Clear:

WARNING: EYE, SKIN AND RESPIRATORY IRRITANT.. Contains acrylic polymer and ethylene glycol. Harmful if swallowed. Long term exposure to ingredients in this product can increase the risk of certain cancers. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate personal protective equipment. **First Aid:** If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush eyes with water for 15 minutes; contact physician. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Material Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

Colors

WARNING: EYE, SKIN AND RESPIRATORY IRRITANT. Contains acrylic polymer, limestone, titanium dioxide, ethylene glycol and benzyl butyl phthalate. Harmful if swallowed. Long term exposure to ingredients in this product can increase the risk of certain cancers. Adverse reproductive effects have been reported in animals. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate personal protective equipment. **First Aid:** If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush eyes with water for 15 minutes; contact physician. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Material Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ordering Information

Part No.	Size	Weight	UPC	Case UPC	Units Per Package	Packages Per Pallet
8301	10.1 Oz. Cartridge - White	14.82	037083083019	10037083083016	12	108
8311	10.1 Oz. Cartridge - Almond	15.42	037083083118	10037083083115	12	108
8321	10.1 Oz. Cartridge - Brown	15.00	037083083217	10037083083214	12	108
8331	10.1 Oz. Cartridge - Clear	10.01	037083083316	10037083083313	12	108
8341	10.1 Oz. Cartridge - Gray	15.00	037083083415	10037083083412	12	108
8351	10.1 Oz. Cartridge - Woodtone	15.00	037083083514	10037083083511	12	108
8361	10.1 Oz. Cartridge - Black	15.42	037083083613	10037083083610	12	108
8371	10.1 Oz. Cartridge - Antique White	15.15	037083083712	10037083083719	12	108

Important Notice: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.

2020 Bruck Street, Columbus, Ohio 43207
CUSTOMER SERVICE 1-800-669-4583
TECH SERVICE 1-800-347-4583
www.titebond.com

Franklin International